



INSIDE DIA. IN.	JOINT DIA. IN.	JOINT DEPTH IN.	GASKET DIA. IN.	WALL 'T' IN.	WEIGHT LBS./ FT.	LAID LENGTH FT.
36	39	3-3/8	21/32	4-3/4	646	20.03
42	45	3-3/4	21/32	4-1/2	698	20.03
48	51-1/4	3-7/8	21/32	5	885	20.03
54	57-3/4	4-1/8	25/32	5-1/2	1092	20.03
60	63-7/8	4-1/4	25/32	6-3/4	1504	20.03
66	70-1/8	4-3/8	25/32	7-1/4	1773	20.03
72	76-3/8	4-1/2	25/32	7-3/4	2063	20.03
78	82-1/2	4-5/8	25/32	8-1/4	2375	20.04
84	88-3/4	4-7/8	25/32	8-3/4	2709	20.04
90	94-7/8	4-7/8	25/32	9-1/4	3193	20.04
96	101-1/8	5-1/8	25/32	9-3/4	3467	20.04
102	106-7/8	4-7/8	25/32	10-1/4	3868	16.04
108	113-1/8	6-1/4	25/32	10-3/4	4257	16.04

NOTES:

1) STANDARD SPECIFICATION AWWA C-300.

NO.	DATE	REVISION DESCRIPTION	DR.	CK.

**VIANINI** PIPE, INC.

36" THRU 108" V-3  
 REINFORCED CONCRETE CYLINDER PIPE  
 WITH RUBBER & STEEL JOINTS